

IN RE APPLICATION OF:

Ucan

STATEMENT OF BASIS FOR

CASE:

OST-031242

RELEVANCE OF

SERIAL NO.:

10/708,343

FOREIGN LANGUAGE

FILED ON:

February 25, 2004

DOCUMENTS

FOR:

SENSOR DEVICE ON A FEED

IDENTIFIED IN SUBMITTED PTO-

PIPELINE CARRYING HIGH

1449

VOLTAGE

COMMISSIONR FOR PATENTS

P.O. Box 1450

Alexandria, VA 22313-1450

ATTENTION OF:

EXAMINER:

Dear Sir:

If any charges or fees must be paid in connection with the following communication, they may be paid out of our Deposit Account No. 50-0545.

Publication Number

Publication Date

Basis for Relevance

EP 1 319 439 A1

December 9, 2002

Magneto-optical sensor arrangement for detecting the position or movement of a scraper or other such moving body (12) beneath a high voltage component in a coating plant.

Accordingly the polarization direction of linearly polarized light waves is changed due to the magnetic field sensed by a sensor element (15) that detects the signals of a magnetic signal element (14) attached to the moving body by use of the Faraday or Kerr effects. The resultant light signals are transmitted over an optical fiber (16) to a remote electronic analysis device.

FACTOR & LAKE, LTD. 1327 W. Washington Blvd., Suite 5 G/H Chicago, IL 60607 (312) 226-1818 (312) 226-1919 (fax)

Jody L. Factor	34157
Micheal D. Lake	33727
William J. Lenz	44208
Joseph M. Kinsella Jr.	45743
Jacob D. Koering	51890
Nick Lee	54260

DE 197 38 097 C2

January 27, 2000

The method involves measuring the earth leakage current in the powder discharged from the spray devices (66). The current level is used as a measure for controlling the extraction equipment. Several units may be coupled together for control and measurement over a bus network.

DE 44 06 046 C2

November 20, 1997

A speed measurement arrangement measures the speed of the gas-powder mixture in the supply line. A mass measurement arrangement measures the mass per unit vol. in a section of the supply line. A computer derives the powder mass flow from the measured speed, the measured mass per unit vol. and the dimensions of the supply line. The speed measurement arrangement has two electrodes arranged at a distance apart along the supply line which detect charge variations on the line caused by the powder-gas mixture, from which the speed is derived. The mass measurement arrangement contains a microwave resonator (36) which detects a change in dielectric constant and/or microwave absorption in a resonant vol. of the supply line (10) as a change in the microwave amplitude or resonant frequency, from which the quantity of powder in the resonant vol. is derived.

DE 44 05 662 A1

February 2, 1995

The system includes an electrically isolated electrically less-conductive component fluidflow course and an electrically-grounded electrically more-conductive component fluidflow course. The electrically more-conductive component fluid-flow course may be additionally electrically isolated at the preference of an operator. A mixer is positioned proximal to an electrostatic spray gun, with a conduit holding alternating segments of electrically more-conductive component and electrically less-conductive component. The alternating segments function in series to additively provide a combined resistance which electrically blocks the high-voltage potential generated at the electrostatic spray gun. This, in turn, effectively isolates the electrically more-conductive component fluid-flow course and electrically less-conductive fluid-flow course from the highvoltage potentials.

DE 39 01 891 A1

July 26, 1990

The electrostatic field strength monitor detects the electrostatic field between a HV spray electrode (14) (12) and the earthed workpiece to be coated. The voltage at the spray electrode (12) or a proportional voltage is applied to a parallel circuit (13) comprising a capacitor (13a) and a light bulb (13b) comprising a capacitor (13a) and a light bulb (13b) with the optical signal provided by the latter fed via an optical fibre coupling (14) to an optoelectrical converter (15). This provides an electrical signal (15a) for a display and/or a switch element and/or a regulator. Pref. the parallel circuit (13) lies between a sensor electrode (16), spaced from the spray electrode (12) on earth.

EP 1 232 799 A2

February 6, 2002

The spray device has at least one separation point (T1, T2, T3) for removal of a part (1,2,3) of the spray device incorporating control or signaling devices (MV, HNS) coupled to incorporated electrical lines (5, 5'), with an electrical coupling device (IK) for the latter provided at the separation point. The electrical coupling device uses inductive coils embedded in the cooperating parts of the spray device and aligned with one another when the parts of the spray device are assembled.

Should anything further be required, a telephone call to the undersigned at (312) 226-1818 is respectfully invited.

Respectfully submitted,

FACTOR & LAKE, LTD.

Dated: July / , 2004

Jacob D. Koering

One of Attorneys for Applicant

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited with the United States Patent Postal Service as first class mail in an envelope addressed to: Commissioner for Patents P.O. Box 1450, Alexandria, VA 22313-1450 on July _______, 2004.

Jacob D. Koering

Name of Applicant, assignee, applicant's attorney or Registered Representative

PTO/SB/08A (06-03)

Approved for use through 07/31/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE er the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

OST-031242

Complete if Known Substitute for form 1449A/PTO 10/708,343 **Application Number** INFORMATION DISCLOSURE 02/25/2004 Filing Date STATEMENT BY APPLICANT First Named Inventor Ucan Art Unit (use as many sheets as necessary) **Examiner Name**

Attorney Docket Number

Sheet

1	U.S. PATENT DOCUMENTS					
F	0.1	Document Number	Publication Date	Name of Patentee or	Pages, Columns, Lines, Where Relevant Passages or Relevant	
Examiner Initials*	Cite No.1	Number - Kind Code ^{2 (if known)}	MM-DD-YYYY	Applicant of Cited Document	Relevant Passages or Relevant Figures Appear	
		US-				
		US-				
		US-				
		U\$-				
		US-			·	
		US-				
		US-				
		US-				
		US-				
		US-				
		US-				
		US-				
		US-				
		US-				
		US-				
		US-				
		US-				

	FOREIGN PATENT DOCUMENTS					
Examiner Initials*	Cite No.1	Foreign Patent Document Country Code ³ - Number ⁴ - Kind Code ⁵ (<i>if known</i>)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	T⁵
		EP 1 319 439 A1	12/09/2002	Duerr Systems GmbH		
		DE 197 38 097 C2	01/27/2000	Wagner Int AG		
		DE 44 06 046 C2	11/20/1997	Wagner Int AG		1
		DE 44 05 662 A1	02/02/1995	Feitel A; Graco Inc.		
		DE 39 01 891 A1	07/26/1990	Wagner Int AG		
		EP 1 232 799 A2	02/06/2002	Duerr Systems GmbH		

Examiner	Date	
Signature	Considered	

EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. 'Applicant's unique citation designation number (optional). 'See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. 'Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). 'For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. 'Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. 'Applicant is to place a check mark here if English language Translation is attached.

Translation is attached.

This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.